



ORLANDO - OLR

OLR: ORLANDO REMOTE COMPRESSOR



Features & Benefits:

- Medium capacity Semi Multi-Deck is convenient for several applications and does not compromise full outlook of the store.
- Waterfall Air Curtain with multi-dimensional blast maintains even temperature.
- Durable Galvanneal Steel Structure with powder coating for additional protection. (Choose any RAL color. Outside and inside can be coated different color at no additional cost.)
- Different temperature ranges can be set according to application: $+8^{\circ}$ C to 0° C.
- Easy Maintenance; reduce labor time and costs with easy access under the Display Case.
- Attractive Bumper system for protection.
- End-Cap with glass available for extended product display.

















FMDC-SS.EN M-OLR P1703

OLR: ORLANDO REMOTE COMPRESSOR







Standard Options:

- Available Heights: S (Small-1300mm), M (Medium-1600mm)
- Lengths: 12 (1250mm) 18 (1875mm), 25 (2500mm),
 37 (3750mm) can be joined together to meet layout requirements.
- Merchandising Flexibility with adjustable shelf heights and angles. Up to 3 (2 shelves plus lower deck) for S (Small 1300mm) or up to 4 (3 shelves plus lower deck) for M (Medium 2180mm).
- Lighting: T8 Fluorescent electronic ballasts do not flicker.
 Canopy and shelving are controlled separately which is convenient when using Motion Activated Lighting "MAL" option.
- Hidden, retractable Night Curtain saves additional energy.
- Clear plastic Shelf-Stops (20mm) keep attractive display and hold price-tags.
- End Wall Panels available: Polyurethane, Polyurethane w/ mirror inside or Polyurethane w/Arc Glass.
- Timed-Off Defrost delivers lower energy consumption and operation costs.*
- Thermostatic Expansion Valve with Balanced Port for better control of superheat. (Danfoss or Sporlan Brand)
- Fan Motor: EBM brand, AC type (Standard Efficiency).
- High efficiency coil design with corrugated aluminum fins and variable spacing augment efficiency and allow for more frost build-up before Defrosting becomes necessary.
- Controllers: Carel brand standard.


Additional Options:


- Lighting: Warm Fluorescent (recommended for meat application) or White LED.
- "MAL" Motion Activated Lighting on Shelves.
- Lower Deck Dividers: Powder Coated Steel Wire or Organic Glass.
- Defrost: Electric or Hot Gas.**
- EV2 electronic Expansion Valve saves up to 10% energy (Carel brand.).*
- Fan Motor: EBM brand, EC type (High Efficiency) GreenTech technology can reduce the fan power consumption up to 70%.
- Controllers: Various Carel or other brand options available.


^{*}For specific control type. Contact us for more details.

^{**} Meat/Fresh Fish application requires Electric or Gas Defrost. Refer to our technical sheet for specific information.


S: SMALL HEIGHT (1300mm)









M: MEDIUM HEIGHT (1600mm)







- 1. Night Curtain
- 2. Canopy Light
- 3. Air Curtain
- 4. Shelf Light
- 5. Adjustable Shelf

- 6. Coil
- 7. Plenum
- 8. Fan Motor
- 9. Drain
- 10. Electrical box


| CAPACITIES ACCORDING TO AHRI 1200 STANDARD GUIDELINES | | | | | | |
|---------------------------------------------------------|-------------------|--------------------|--------------------|--------------------|--------------------|-----------------------|
| Length | | 12 (1250mm) | 18 (1875mm) | 25 (2500mm) | 37 (3750mm) | Ae I: Intermediate |
| SMALL HEIGHT | | | | | | |
| DA: (Display Area)* | (m²) | 1.04 | 1.56 | 2.08 | 3.12 | 0.23 |
| RV: (Refrigerated Volume)** | (m³) | 0.444 | 0.665 | 0.887 | 1.331 | n/a |
| MEDIUM HEIGHT | | | | | | |
| DA: (Display Area)* | (m ²) | 1.39 | 2.09 | 2.78 | 4.17 | 0.37 |
| RV: (Refrigerated Volume)** | (m³) | 0.603 | 0.905 | 1.207 | 1.810 | n/a |

TDA: (Total Display Area) = DA + Ae

Ae = Projected area from End Wall Panel w/Glass









4: 220V / 3PH / 50HZ

8: 115V / 1PH / 60HZ

1: 208-230V / 3PH / 60HZ

7: 220V / 1PH / 50HZ

CORPORATE OFFICE: 4362 Thurmon Tanner Parkway / Flowery Branch, GA 30542 / USA
Tel.: + 1-678-714-6991 / Fax: +1-678-714-2357 / Toll Free: 1-855-374-2660
Venezuela: (0251) 710 5067 / Colombia: (1) 381 9070 / Mexico: (55) 4161 3805
Dominican Republic: (829) 954 8425 / Peru: (1) 705 6209 / info@friconusa.com / www.friconusa.com

6: 208-230V / 1PH / 60HZ

9: "S" Special Voltage